

Android 11

E-1 model

TA-75



Display	
Display size	75"
Display type	DLED
Aspect ratio	16:9
Screen display size	1649.7×927.9 (mm)
Physical resolution	4K 3840×2160
Display color	10bit/1.07 Billion
Refresh rate	60Hz
Brightness	400cd/m ²
Contrast	4000:1
Response time	6ms
Viewing angle	178° (H) / 178° (V)
Display protection	4mm full tempered high explosion-proof glass
Backlight life	50000 hours

Screen characteristic	
Overall dimensions	1705*1013.5*130 (mm, L*W*T)
Consumption rate	≤230W(not including ops)
Standby power	≤1W
Voltage range	AC100-240V~50/60Hz
Net weight	54kg
Gross weight	63kg
Packaging size	1860*1210*230 (mm, L*W*T)
VESA	600 x400 mm
Speaker specifications	15W × 2
Microphone	Built-in 6 array

Accessories	
Power cable	1pcs
Remote control	1pcs
Wall mount	1pcs
HDMI & Touch USB	1pcs
VGA Cable	1pcs
Whiteboard pen	2pcs

System parameters	
CPU	Quad-core ARM Cortex-A55
System version	Android 11.0 system
RAM	4GB
ROM	32GB
Back Input interface	2*HDMI IN, 1*USB2.0, 1*USB3.0, 1*AV IN, 1*RJ45, 1*RS232, 1*USB Touch, 1*YPBPR, 1*VGA IN, 1*VGA Audio IN
Back Output interface	1*Earphone, 1*AV OUT, 1*SPDIF OUT
Front input interface	1*HDMI IN, 1*USB Touch, 3*USB3.0, 1*Type-C
WIFI	Support IEEE 802.11 a/b/g/n/ac/ax, 2.4G Hz/ 5G Hz
Bluetooth	√

Basic parameters	
Touch sensing	Infrared sensing positioning recognition touch technology, HID free drive
Writing method	Fingers, touch pens or other non-transparent objects not less than 5mm in diameter, support 20 points finger touch
Positioning accuracy	More than 90% of the touch area is ≤1mm
Reaction time	<6ms
Communication	Support USB 2.0 (FULL SPEED) HID Compliant (Plug & Play) Touch PC Interface
Touch resolution	32768*32768
Times of touches	Unlimited time in theoretical
Transfer speed	12Mb/s
Driver	Automatic system identification, free drive
Operating system	Support windows, Android, Mac OS, Linux
Operating temperature	0℃-40℃
Feature	Palm Rejection, Support 4 devices to connect the panel via EShare wireless casting application, Free eClass educational software installed in computer
Certificate	CE, FCC, RoHS

Details are subject to change without notice

DIMENSIONS

75''

